



CLEAT SELECTOR CHART

ADD PREFIX 385LSF TO REFERENCE SIZE FOR ORDERING REF.

	FOR LSF ARMoured CABLES TO BS 6724 600/1000V STRANDED COPPER CONDUCTORS (SIZE mm ²)														
	1.5	2.5	4	6	10	16	25	35	50	70	95	120	150	185	240
2 CORE	01	01	02	03	04	04	04	05	05	05	06	07	07	08	08
3 CORE	01	01	02	03	04	04	05	06	06	06	07	07	08	08	--
4 CORE	01	02	03	04	04	05	06	06	06	07	08	08	08	--	--

TEL/CLEAT SIZE 01 TO 04 USE M4 MACHINE SCREWS OR No. 8 WOOD SCREWS

TEL/CLEAT SIZE 05 TO 08 USE M6 MACHINE SCREWS OR No. 12 WOOD SCREWS

ADD PREFIX 385LSF TO REFERENCE SIZE FOR ORDERING REF.

	XLPE ARMoured CABLES TO BS 5467 600/1000V STRANDED COPPER CONDUCTORS (SIZE mm ²)														
	1.5	2.5	4	6	10	16	25	35	50	70	95	120	150	185	240
2 CORE	01	01	02	03	03	04	04	05	05	05	06	07	07	08	08
3 CORE	01	01	02	03	04	04	05	06	06	06	07	07	08	08	--
4 CORE	01	02	02	03	04	05	06	06	06	07	08	08	08	--	--

IMPORTANT NOTE : THE DIMENSIONS OF CABLES VARY WITH MANUFACTURING TOLERANCES. WE ADVISE THE CABLE DIAMETER IS MEASURED WHERE POSSIBLE BEFORE PURCHASING. THE RECOMMENDATIONS HERE ARE GIVEN IN GOOD FAITH BUT PIRELLI CABLES LTD CANNOT BE HELD LIABLE FOR MISTAKES IN SELECTION HOWEVER CAUSED.

Manufactured by Pirelli Cables Ltd, Component Unit, PO Box 4, Hall Lane, Prescott, Merseyside, L34 5UR, United Kingdom